

**PD 320 LOCATION OF COMMUNICATION TOWERS POLICY**

Originating Document- PL 37-2007

Effective Date- February 19 2007

Last Modified - March 10, 2021

## 1. Location and Height

Freestanding communication antennas, greater than or equal to 15 meters in height, on sites located in the Corporation of the County of Prince Edward (the municipality) shall be subject to a consultation process conducted by the carrier, with the surrounding property owners as required by Industry Canada CPC-2-0-03 - Radiocommunication and Broadcasting Antenna Systems, dated July 15, 2014.

## 2. Co-utilization

All applicants for freestanding antenna structures will be requested to identify any other structure within a radius of 1 kilometre of the proposed location and to provide documentary evidence that co-utilization of the existing or new single structure is not a viable alternative to a second structure.

## 3. Community Consultation Process

3.1 The carrier shall notify the municipality, in writing with specific information on the location, type and size of proposed structure, as well as the name and telephone number of the contact person.

3.2 The municipality shall notify all property owners within five (5) times the proposed height of the structure or one (1) kilometre, whichever is greater, with the information provided from the carrier on the location, type and size of proposed structure, as well as the name and telephone number of the application contact person.

3.3 The notification shall be;

- a) sent by regular mail and/or hand delivered to all affected property owners as per Section 3.2 above; and,
- b) a newspaper ad in a newspaper of sufficiently general circulation in the affected area.

3.4 The communications to and from the municipality and the carrier shall maintain compliance with information content and timelines as required by Industry Canada CPC-2-0-03 - Radiocommunication and Broadcasting Antenna Systems, dated July 15, 2014, or any such revision to this legislation as may arise.

## 4. Reflective Shields

All communication towers shall be fitted with a comprehensive light reflective shield(s) for 360 degree coverage to a distance of three (3) kilometres for each light to help reduce adverse impact to neighbouring homes.